

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

DATE MAILED: 11/15/2005

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/896,783	06/29/2001	Clyde George Bethea	25-66-105-20-29-1-3-35-14	8896
7590 11/15/2005			EXAMINER	
	Lucent Technologies Inc.		LI, SHI K	
	strator (Room 3J-219)		ADTIBUT	DA DED MUMDED
101 Crawfords Corner Road			ART UNIT	PAPER NUMBER
Holmdel, NJ ()7733		2633	

Please find below and/or attached an Office communication concerning this application or proceeding.

		(k)
	Application No.	Applicant(s)
	09/896,783	BETHEA ET AL.
Office Action Summary	Examiner	Art Unit
	Shi K. Li	2633
The MAILING DATE of this communication	appears on the cover sheet	with the correspondence address
Period for Reply	DLV IO OFT TO EVOIDE AL	
A SHORTENED STATUTORY PERIOD FOR RE WHICHEVER IS LONGER, FROM THE MAILING - Extensions of time may be available under the provisions of 37 CFF after SIX (6) MONTHS from the mailing date of this communication. - If NO period for reply is specified above, the maximum statutory period to reply within the set or extended period for reply will, by straining reply received by the Office later than three months after the mearned patent term adjustment. See 37 CFR 1.704(b).	B DATE OF THIS COMMUN R 1.136(a). In no event, however, may a riod will apply and will expire SIX (6) MO atute, cause the application to become	IICATION. a reply be timely filed DNTHS from the mailing date of this communication. ABANDONED (35 U.S.C. § 133).
Status		
1) Responsive to communication(s) filed on 0	6 September 2005.	
	his action is non-final.	
3) Since this application is in condition for allo	wance except for formal ma	tters, prosecution as to the merits is
closed in accordance with the practice under	er <i>Ex parte Quayle</i> , 1935 C.	D. 11, 453 O.G. 213.
Disposition of Claims		
4)⊠ Claim(s) <u>1-3 and 6-24</u> is/are pending in the	annlication	
4a) Of the above claim(s) is/are without state with the	• •	
5) Claim(s) is/are allowed.		•
6)⊠ Claim(s) <u>1-3 and 6-24</u> is/are rejected.		
7) Claim(s) is/are objected to.		
8) Claim(s) are subject to restriction an	d/or election requirement.	
Annlinetian Daneur		
Application Papers		
9) The specification is objected to by the Exam		hutha Francisca
10) The drawing(s) filed on is/are: a) a Applicant may not request that any objection to		
Replacement drawing sheet(s) including the cor		
11) The oath or declaration is objected to by the		• • • • • • • • • • • • • • • • • • • •
Priority under 35 U.S.C. § 119	•	
12) Acknowledgment is made of a claim for fore	ign priority under 35 U.S.C.	§ 119(a)-(d) or (f).
a) ☐ All b) ☐ Some * c) ☐ None of: 1. ☐ Certified copies of the priority documents.	onto hovo hoon received	•
		Application No.
2. Certified copies of the priority docum3. Copies of the certified copies of the p		
application from the International Bur		n received in this National Stage
* See the attached detailed Office action for a	, , , , , , , , , , , , , , , , , , , ,	t received
555 the attached detailed office action for a	iot of the definied dopies no	
Attachment(s)		
1) X Notice of References Cited (PTO-892)	4) Interview	Summary (PTO-413)
2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	Paper No	(s)/Mail Date
3) Information Disclosure Statement(s) (PTO-1449 or PTO/SB/		Informal Patent Application (PTO-152)
Paper No(s)/Mail Date	6) [_] Other:	

Art Unit: 2633

DETAILED ACTION

Claim Rejections - 35 USC § 103

- 1. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
- 2. Claims 1, 6, 8, 10-13 and 15-19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Paiella et al. (R. Paiella et al., "Generation and Detection of High-Speed Pulses of Mid-Infrared Radiation with Intersubband Semiconductor Lasers and Detectors", IEEE Transactions on Photonics Technology Letters, Vol. 12, No. 7, July 2000) in view of Christopher (U.S. Patent Application Pub. 2002/0181059 A1), Ionov et al. (U.S. Patent 6,816,682 B1) and Miyauchi et al. (U.S. Patent 6,823,141 B2).

Regarding claims 1, 6 and 13, Paiella et al. discloses in FIG. 2 a transmitter comprising a mid-infrared laser (QC laser) for generating a stream of optical pulses according to a stream of input signal. As illustrated in FIG. 2, the QC laser is directly modulated to generate high and low optical power levels as illustrated in FIG. 3. The difference between Paiella et al. and the claimed invention is that Paiella et al. does not teach to use the transmitter to transmit pulses to a remote receiver for free space communication. Christopher teaches in FIG. 23 a free space communication system using 10-micro optical link. Christopher teaches in paragraph [0058] that mid-infrared wavelength is preferable over near-infrared for free-space communication because it has less attenuation over fog conditions. One of ordinary skill in the art would have been motivated to combine the teaching of Christopher with the mid-IR transmitter of Paiella et al. and apply the mid-IR transmitter to transmit optical pulses over free space channel to a remote receiver because mid-IR pulses have less attenuation over fog conditions and the transmitter of

Art Unit: 2633

Paiella et al. generates short pulses and supports high data-rate communication. Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the mid-IR transmitter of Paiella et al. for free space communication, as taught by Christopher, because mid-IR pulses have less attenuation over fog conditions and the transmitter of Paiella et al. generates short pulses and supports high data-rate communication.

The modified free space communication system of Paiella et al. and Christopher still fails to teach receiving a stream of input data signals since Paiella et al. only uses FIG. 2 to demonstrate the operation theory. Ionov et al. discloses in FIG. 2 a real optical transmitter 48 that received input data signals form sorter 42. One of ordinary skill in the art would have been motivated to combine the teaching of Ionov et al. with the modified free space communication system of Paiella et al. and Christopher because a real system transmits data and generates revenue. Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to transmit real data signals received by the optical transmitter, as taught by Ionov et al., in the modified free space communication system of Paiella et al. and Christopher because a real system transmits data and generates revenue.

The modified free space communication system of Paiella et al., Christopher and Ionov et al. still fails to teach RZ-coded transmission. It is well known in the art that digital data can be transmitted using NRZ signal or RZ signal. For example, Miyauchi et al. teaches explains the in FIG. 3A and FIG. 3B NRZ and RZ signals. FIG. 3A shows that in RZ signal the duration of a non-lasing state representing 0 is longer that the lasing interval representing 1. One of ordinary skill in the art would have been motivated to use RZ format for digital transmission because RZ-coded signal is lesser affected by the inter-symbol interference due to the increase of the width of

Art Unit: 2633

pulses on the transmission line than the NRZ coded signal (see col. 5, lines 49-51 of Miyauchi et al.). Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use RZ-coded signal for digital data transmission, as taught by Miyauchi et al., in the modified free space communication system of Paiella et al., Christopher and Ionov et al. because RZ-coded signal is lesser affected by the inter-symbol interference due to the increase of the width of pulses on the transmission line than the NRZ coded signal.

Regarding claims 8 and 17-18, Christopher suggests a wavelength of 10 microns.

Regarding claims 10 and 19, both Christopher and Paiella et al. teach that mid-infrared light has low atmospheric losses (see p. 781, second paragraph of Paiella et al.).

Regarding claim 11-12, Paiella et al. teaches a QC laser which operates at around 3 GHz (see p. 781, right col., first paragraph).

Regarding claim 15, Paiella et al. teaches in FIG. 2 and FIG. 3 that the laser output is at a high optical power level when the laser is driven above a lasing threshold, and the laser output is at a low optical power level when the laser is below the lasing threshold. Paiella et al. teaches on page 781, right col., last paragraph that the laser is biased at approximately 80% of its CW threshold value.

Regarding claim 16, Paiella et al. teaches a quantum cascade laser.

3. Claims 2, 7 and 9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Paiella et al. (R. Paiella et al., "Generation and Detection of High-Speed Pulses of Mid-Infrared Radiation with Intersubband Semiconductor Lasers and Detectors", IEEE Transactions on Photonics Technology Letters, Vol. 12, No. 7, July 2000) in view of Christopher (U.S. Patent Application Pub. 2002/0181059 A1) and Ionov et al. (U.S. Patent 6,816,682 B1).

Art Unit: 2633

Regarding claim 2, Paiella et al. discloses in FIG. 2 a transmitter comprising a midinfrared laser (QC laser) for generating a stream of optical pulses according to a stream of input signal. As illustrated in FIG. 2, the QC laser is directly modulated to generate high and low optical power levels as illustrated in FIG. 3. Paiella et al. teaches in FIG. 2 and FIG. 3 that the laser output is at a high optical power level when the laser is driven above a lasing threshold, and the laser output is at a low optical power level when the laser is below the lasing threshold. Paiella et al. teaches on page 781, right col., last paragraph that the laser is biased at approximately 80% of its CW threshold value. The difference between Paiella et al. and the claimed invention is that Paiella et al. does not teach to use the transmitter to transmit pulses to a remote receiver for free space communication. Christopher teaches in FIG. 23 a free space communication system using 10-micro optical link. Christopher teaches in paragraph [0058] that mid-infrared wavelength is preferable over near-infrared for free-space communication because it has less attenuation over fog conditions. One of ordinary skill in the art would have been motivated to combine the teaching of Christopher with the mid-IR transmitter of Paiella et al. and apply the mid-IR transmitter to transmit optical pulses over free space channel to a remote receiver because mid-IR pulses have less attenuation over fog conditions and the transmitter of Paiella et al. generates short pulses and supports high data-rate communication. Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use the mid-IR transmitter of Paiella et al. for free space communication, as taught by Christopher, because mid-IR pulses have less attenuation over fog conditions and the transmitter of Paiella et al. generates short pulses and supports high data-rate communication.

Art Unit: 2633

The modified free space communication system of Paiella et al. and Christopher still fails to teach receiving a stream of input data signals since Paiella et al. only uses FIG. 2 to demonstrate the operation theory. Ionov et al. discloses in FIG. 2 a real optical transmitter 48 that received input data signals form sorter 42. One of ordinary skill in the art would have been motivated to combine the teaching of Ionov et al. with the modified free space communication system of Paiella et al. and Christopher because a real system transmits data and generates revenue. Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to transmit real data signals received by the optical transmitter, as taught by Ionov et al., in the modified free space communication system of Paiella et al. and Christopher because a real system transmits data and generates revenue.

Regarding claims 7 and 9, Christopher suggests a wavelength of 10 microns.

4. Claim 3 is rejected under 35 U.S.C. 103(a) as being unpatentable over Paiella et al., Christopher and Ionov et al. as applied to claim 2, 7 and 9 above, and further in view of Hwang et al. (U.S. Patent 6,549,556 B1).

Paiella et al., Christopher and Ionov et al. have been discussed above in regard to claims 2, 7 and 9. The difference between Paiella et al., Christopher and Ionov et al. and the claimed invention is that Paiella et al., Christopher and Ionov et al. do not teach electrical pumping and optical pumping for laser operation. Hwang et al. teaches in col. 1, lines 50-65 operation of semiconductor lasers. A semiconductor laser includes a gain region for building up energy. Various forms of pumping energy may be utilized to cause the active region to emit photons including electrical pumping, optical pumping and electron beam pumping. These are equivalent mechanisms for pumping energy to a semiconductor laser. Where the claimed differences

Art Unit: 2633

involve the substitution of interchangeable or replaceable equivalents and the reason for the selection of one equivalent for another was not to solve an existent problem, such substitution has been judicially determined to have been obvious. See In re Ruff, 118, USPQ 343 (CCPA 1958). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to use either electrical pumping or optical pumping to build up energy in the active region of a semiconductor laser in the modified free space communication system of Paiella et al., Christopher and Ionov et al.

5. Claim 20 is rejected under 35 U.S.C. 103(a) as being unpatentable over Paiella et al., Christopher, Ionov et al. and Miyauchi et al. as applied to claims 1, 6, 8, 10-13 and 15-19 above, and further in view of Durant et al. (U.S. Patent 6,016,212).

Paiella et al., Christopher, Ionov et al. and Miyauchi et al. have been discussed above in regard to claims 1, 6, 8, 10-13 and 15-19. The difference between Paiella et al., Christopher, Ionov et al. and Miyauchi et al. and the claimed invention is that the modified free space communication of Paiella et al., Christopher, Ionov et al. and Miyauchi et al. does not teach collimating optics. However, it is well known in the art to use optics to change the geometry of light beams. For example, Durant et al. teaches in FIG. 1 and col. 3, lines 5-10 to use collimating optics to form a light beam of a diameter of half an inch (13 mm). One of ordinary skill in the art would have been motivated to combine the teaching of Durant et al. with the modified free space optical communication system of Paiella et al., Christopher, Ionov et al. and Miyauchi et al. because an appropriate light beam size makes it easy for alignment while maintains a reasonable size for the optics such as telescope. Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use collimating optics to

Art Unit: 2633

obtain an appropriate geometry for the light beam, as taught by Durant et al., in the modified free space optical communication system of Paiella et al., Christopher, Ionov et al. and Miyauchi et al. because an appropriate light beam size makes it easy for alignment while maintains a reasonable size for the optics such as telescope.

6. Claims 21-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Paiella et al., Christopher, Ionov et al. and Miyauchi et al. as applied to claim 1, 6, 8, 10-13 and 15-19 above, and further in view of Hwang et al. (U.S. Patent 6,549,556 B1).

Paiella et al., Christopher, Ionov et al. and Miyauchi et al. have been discussed above in regard to claims 1, 6, 8, 10-13 and 15-19. The difference between Paiella et al., Christopher, Ionov et al. and Miyauchi et al. and the claimed invention is that Paiella et al., Christopher, Ionov et al. and Miyauchi et al. do not teach electrical pumping and optical pumping for laser operation. Hwang et al. teaches in col. 1, lines 50-65 operation of semiconductor lasers. A semiconductor laser includes a gain region for building up energy. Various forms of pumping energy may be utilized to cause the active region to emit photons including electrical pumping, optical pumping and electron beam pumping. These are equivalent mechanisms for pumping energy to a semiconductor laser. Where the claimed differences involve the substitution of interchangeable or replaceable equivalents and the reason for the selection of one equivalent for another was not to solve an existent problem, such substitution has been judicially determined to have been obvious. See In re Ruff, 118, USPQ 343 (CCPA 1958). Therefore, it would have been obvious to one of ordinary skill in the art at the time of the invention to use either electrical pumping or optical pumping to build up energy in the active region of a semiconductor laser in

the modified free space communication system of Paiella et al., Christopher, Ionov et al. and Miyauchi et al.

7. Claims 14 and 23-24 are rejected under 35 U.S.C. 103(a) as being unpatentable over Paiella et al., Christopher, Ionov et al. and Miyauchi et al. as applied to claim 1, 6, 8, 10-13 and 15-19 above, and further in view of Ramaswami et al. ("Optical Networks: a Practical Perspective" by Ramaswami et al., Academic Press, 1998, pp. 177-180).

Paiella et al., Christopher, Ionov et al. and Miyauchi et al. have been discussed above in regard to claims 1, 6, 8, 10-13 and 15-19. The difference between Paiella et al., Christopher, Ionov et al. and Miyauchi et al. and the claimed invention is that Paiella et al., Christopher and Ionov et al. do not teach percentage of lasing interval. Firstly, percentage of lasing interval depends on data rate. Secondly, Ramaswami et al. teaches in FIG. 4.1 short pulse format which minimize the effects of chromatic dispersion. One of ordinary skill in the art would have been motivated to use short pulse format for digital data transmission because it minimizes chromatic dispersion. Thus it would have been obvious to one of ordinary skill in the art at the time the invention was made to use short pulse format, as taught by Ramaswami et al., in the modified space communication system of Paiella et al., Christopher, Ionov et al. and Miyauchi et al. because it minimizes chromatic dispersion. Paiella et al. teaches in FIG. 3(a) that the pulse width is 89 psec. For a data rate of 1 GHz, the lasing interval is less than 10% of the data period.

Response to Arguments

8. Applicant's arguments with respect to claims 1-3 and 6-24 have been considered but are most in view of the new ground(s) of rejection.

Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Shi K. Li whose telephone number is 571 272-3031. The examiner can normally be reached on Monday-Friday (8:30 a.m. - 5:00 p.m.).

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Jason Chan can be reached on 571 272-3022. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

skl 10 November 2005

> Shi K. Li Patent Examiner